

series filters





"S" series filters

Industrial strength polymer media filters

Thousands of installations over the last 33 years bear testament to the quality and reliability of Poolrite "S" Series filters.

Award Winning V2000

Exclusive to Poolrite filters

- · Over moulded gaskets No spider gasket blow outs
- 50mm ports for greater water flow
- Large diameter valve for greater water flow and quieter operation
- Domed top cover prevents debris build up around valve stem for easy operation and longevity
- Fitted with 50mm plumbing unions allowing quick connection and simplified servicing

S9000

 Heavy duty 50mm multi-port valve for the most demanding residential or commercial installation

Warranty



10 Year filter tank



1 Year on all other components



Poolrite recommends using







Features

- One piece seamless rotationally moulded tank designed for maximum strength
- Made from high density polyethylene for strength & durability
- Clever designed dispersion inlet overdrain for smooth even flow of water into the filter tank
- Later underdrain design ensures maximum flow for fast and efficient backwashing which increases time between backwash cycles
- All non-corrosive construction suitable for all types of sanitation
- Australian design & manufacture

Specifications


S-5000






S-6000





S-9000





MODEL	S-5000	S-6000	S-9000
Filter Tank Diameter	522mm (20 in)	635mm (25 in)	813mm (32 in)
Max Flow Rate (L/hr)			
Diamond Kleen media M10 fine (kgs)	45	90	150
Diamond Kleen media M20 coarse (kgs)			
Recommended Pump Model	SQI-400	SQI-500 /	SQI-700





