

# LEISURETIME<sup>®</sup> II

## SAND FILTER

SO CLEAN, SO CLEAR, SO EASY.

The LeisureTime<sup>®</sup> II Fibreglass Sand Filter is the perfect high performance sand filter, it's incredibly simple to operate and maintain, and it's built with long-term reliability in mind. Plus its highly efficient design provides all the clean, crystal clear water your pool requires, year after year.





## KEY FEATURES

- Spun-woven fibreglass construction for exceptional strength, chemical resistance and long life.
- UV resistant tank.
- Stainless steel clamp for corrosion resistance and allows 360° rotation of multi-port valve to simplify installation.
- Top diffuser ensures even distribution of water over the top of the sand bed.
- Top Mount, 6 function, 1-1/2" /40mm multi-port valve features a pressure gauge, sight glass and manual air relief for optimal filtration efficiency. Large capacity models 25" up to 32" are available with a 2" /50mm valve.
- Internal design ensures that water is exposed to maximum sand surface area for superior filtration performance and efficient backwashing.
- 10 year pro-rata warranty\*.

\*Terms & conditions apply.

### How the LeisureTime® II Sand Filter works:

Pool water is routed through the sand filled pressure vessel. The sand traps particles so small they are undetectable to the naked eye. Over time, dirt accumulates in the spaces between the sand particles, causing the pressure in the vessel to rise.

This signals you to "backwash" the filter. Simply reverse the water flow and "knock out" the dirt.



### 6 FUNCTION MULTI-PORT VALVE

- Filter
- Backwash
- Rinse
- Waste
- Closed
- Re-circulate

### UV RESISTANT FIBREGLASS BODY

For exceptional strength, chemical resistance and long life.

### STAINLESS STEEL CLAMP

For corrosion resistance and allows 360 degree rotation of multi-port valve.

Filter Model	Filter Area	MPV	Sand Required (Kg)	Zeolite Required (Kg)	Glass Required		Max Flow (LPM)	Min BackWash (LPM)
					Coarse (Kg)	Fine (Kg)		
LSFII-21-40	0.22m <sup>2</sup>	1-1/2" / 40mm	85	70	30	45	185	120
LSFII-25-40	0.32m <sup>2</sup>	1-1/2" / 40mm	145	105	45	75	260	180
LSFII-25-50	0.32m <sup>2</sup>	2" / 50mm	145	105	45	75	270	180
LSFII-28-50	0.41m <sup>2</sup>	2" / 50mm	210	165	60	120	345	230
LSFII-32-50	0.5m <sup>2</sup>	2" / 50mm	355	270	90	225	420	285



1-21 Monash Drive | Dandenong South, VIC 3175 | Australia | 1300 137 344 | [pentairpool.com.au](http://pentairpool.com.au)

Information contained here-in remains the property of Pentair under Australian copyright law. Content may not be reproduced or transmitted without our prior written permission. All indicated Pentair trademarks and logos are property of Pentair. Third party registered and unregistered trademarks/logos are the properties of their respective owners.

Disclaimer: Pentair reserves the right to change product specifications and products details. Product images are for reference purposes only and may not represent the actual/current product.

©2022 Pentair. All rights reserved.